

Alnor Systemy Wentylacji Sp. z o. o.
ul. Zwierzyniecka 8b
00-719 Warszawa
tel.: (022) 737 40 00, fax: (022) 737 40 04
alnor@alnor.com.pl, www.alnor.com.pl

Typ	Wymiary szer. x wys. /średnica [mm]		Zakres wydajności
Anemostaty			
Anemostaty nawiewne kwadratowe			
NCD-S	295x295	150x150	170-300 m ³ /h
	370x370	225x225	380- 670 m ³ /h
	445x445	305x305	680-1190 m ³ /h
	520x520	380x380	1060-1855 m ³ /h
	595x595	455x455	1530-2680 m ³ /h
Anemostaty kasetonowe wirowe			
NKSD-C	298x298-/8 otworów		72-252 m ³ /h
	396x396/16		162-540 m ³ /h
	498x498/24		252-1080 m ³ /h
	598x598/48, 24		360-1080 m ³ /h
Anemostaty nawiewne okrągłe			
NCD	Ø 150 - Ø 350		
Nawiewniki sufitowe			
FKD	160-630		300-7000 m ³ /h
CRL/CRS	Ø 100 - Ø 400		50-1500 m ³ /h
Kratki			
Kratki zewnętrzne lub wewnętrzne aluminiowe lub z blachy kwasoodpornej			
USAV	Ø 100 - Ø 200		70-800 m ³ /h
USUF	Ø 100 - Ø 150		57-138 cm ²
USSE	110x54, 205x61		28-42 cm ²
Kratka podłogowa			
ULMA-100	Ø 100		45 cm ²
ULMA-125	Ø 125		67 cm ²
ULMA -150	Ø 150		115 cm ²
Kratki do kanałów okrągłych			
RGS	325x75 do 1225-225		100-4000 m ³ /h
Dysze			
NDZ-200	Ø 198		400-1100 m ³ /h
NDZ-250	Ø 248		400-1500 m ³ /h



NCD



NCD-S



NDZ



NKSD-C



ULMA



USAV



RGS



FKD