



Cleanliness Classification of Ventilation Products

ALNOR-SYSTEMY WENTYLACJI SP. Z O.O.

The classification committee appointed by Rakennustietosäätiö RTS sr has approved product:

Pressed fittings: coupling MSF (0.5-1.0 mm; ø 80-1600 mm)
Pressed fittings: end caps CPSL, CPF 0.5 mm; ø 80-250 mm
Pressed fittings: reducer RPCFL (thickness 0,5–1mm, Ø 80–315mm)
Pressed fittings: reducer RPCL (thickness 0,5–1mm, Ø 80–315mm)
Pressed fittings: saddle SPL 0.5 mm; ø 80-630 mm
Pressed fittings: spigot plate KILL 0.5-1.0 mm; ø 80-630 mm
Pressed fittings: Take-off ILPRL (thickness 0,5–1mm, Ø 80–315mm)
Pressed fittings: take-off pieces ILPL 0.5 mm; ø 80-200 mm
Pressed fittings: T-piece TPCL (thickness 0,5–1mm, Ø 80–315mm)
Pressed fittings; coupling SNSL, SMSFL (0.5-0.6 mm; ø 100-630 mm)

to Cleanliness Class M1. The classification is valid until **29.10.2027**.

ALNOR-SYSTEMY WENTYLACJI SP. Z O.O. has the right to mark its classified products with the classification label and to use the classification label in the marketing of these products. The classification decision is based on documents Classification of Indoor Environment 2018, and Cleanliness Classification of Ventilation Products, General rules.

Rakennustieto Oy

Laura Apilo
CEO

Jukka Seppänen
Secretary of the Classification
Committee

RAKENNUSTIETO

Rakennustieto Oy

Malminkatu 16 A, FI-00100 Helsinki | tel. +358 45 490 0747 | m1@rakennustieto.fi | ymparisto.rakennustieto.fi