



## CLEANLINESS CLASSIFICATION OF AIR-HANDLING COMPONENTS

### ALNOR-SYSTEMY WENTYLACJI SP. Z O.O.

The classification working group set up by The Building Information Foundation RTS sr has approved the following product:

- Segmented fittings: bend BSL (15°, 30°, 45°, 60°, 90°, thickness 0,5-1,5mm, Ø 200-1600mm)**
- Segmented fittings: bend BSKL (15°, 30°, 45°, 60°, 90°, thickness 0,5-1,5mm, Ø 200-1600mm)**
- Segmented fittings: bend BSDL (15°, 30°, 45°, 60°, 90°, thickness 0,5-1,5mm, Ø 200-1600mm)**
- Segmented fittings: flat reduction RSFC (thickness 0,5-1,5mm, Ø 80-1600mm)**
- Segmented fittings: flat reduction RSFCFL (thickness 0,5-1,5mm, Ø 80-1600mm)**
- Segmented fittings: flat reduction RSFL (thickness 0,5-1,5mm, Ø 80-1600mm)**
- Segmented fittings: flat reduction RSFFL (thickness 0,5-1,5mm, Ø 80-1600mm)**
- Segmented fittings: reducer RSCLL (thickness 0,5-1,5mm, Ø 80-1600mm)**
- Segmented fittings: reducer RSLL (thickness 0,5-1,5mm, Ø 80-1600mm)**
- Segmented fittings: reducer RSCLFL (thickness 0,5-1,5mm, Ø 80-1600mm)**
- Segmented fittings: collar saddle SSCL (thickness 0,5-1,5mm)**
- Segmented fittings: collar saddle SSL (thickness 0,5-1,5mm)**
- Segmented fittings: saddle tee SSCBBL (thickness 0,5-1,5mm)**
- Segmented fittings: saddle tee SSCFBL (thickness 0,5-1,5mm)**
- Segmented fittings: T-piece XPCL (thickness 0,5-1,5mm, Ø 80-1600mm)**
- Segmented fittings: T-piece TPCL-CP-R (thickness 0,5-1,5mm, Ø 80-1600mm)**
- Segmented fittings: T-piece TPCL-CP-R-I (thickness 0,5-1,5mm, Ø 80-1600mm)**
- Segmented fittings: T-piece TSCL (thickness 0,5-1,5mm, Ø 80-1600mm)**
- Segmented fittings: T-piece TSL (thickness 0,5-1,5mm, Ø 80-1600mm)**
- Segmented fittings: T-piece TSVL-45 (thickness 0,5-1,5mm, Ø 80-1600mm)**

**Segmented fittings: T-piece XSVL-45 (thickness 0,5-1,5mm, Ø 80-1600mm)**  
**Segmented fittings: T-piece XSCL (thickness 0,5-1,5mm, Ø 80-1600mm)**  
**Segmented fittings: T-piece XSL (thickness 0,5-1,5mm, Ø 80-1600mm)**  
**Segmented fittings: Y-piece YSVL-45 (thickness 0,5-1,5mm, Ø 80-1600mm)**  
**Segmented fittings: take-off ILSVL-45 (thickness 0,5-1,5mm, Ø 80-1250mm)**  
**Segmented fittings: take-off ILSNL (thickness 0,5-1,5mm, Ø 80-1250mm)**  
**Segmented fittings: take-off ILSL (thickness 0,5-1,5mm, Ø 80-1250mm)**  
**Segmented fittings: take-off ASVL-45 (thickness 0,5-1,5mm, Ø 80-1250mm)**  
**Segmented fittings: male coupling NSL (thickness 0,5-1,5mm, Ø 80-1600mm)**  
**Segmented fittings: coupling with gasket SNSL (thickness 0,5-1,5mm, Ø 80-1250mm)**  
**Segmented fittings: coupling with gasket SMSFL (thickness 0,5-1,5mm, Ø 80-1250mm)**  
**Segmented fittings: lateral pressed saddle SSCVL-45 (thickness 0,5-1,5mm, Ø 80-1250mm)**  
**Segmented fittings: setoff ODSOL (thickness 0,5-1,5mm, Ø 80-1250mm)**  
**Segmented fittings: regulation damper DARL**  
**Segmented fittings: adjusting and shut-off damper DASML**  
**Segmented fittings: adjusting and shut-off damper DASL**  
**Segmented fittings: adjusting and shut-off damper DASL-CV**  
**Segmented fittings: adjusting and shut-off damper DATL**  
**Segmented fittings: adjusting and shut-off damper DAPL-CV**  
**Segmented fittings: backdraught damper DAOSL**  
**Segmented fittings: sliding damper GKL (thickness 1-3mm)**  
**Segmented fittings: sliding damper GKML (thickness 1-3mm)**  
**Segmented fittings: steel multi-blade damper DASQL**  
**Segmented fittings: steel multi-blade damper DASQML**

as belonging to cleanliness class M1 for air-handling components.

The classification is valid until 11.10.2023.

ALNOR-SYSTEMY WENTYLACJI SP. Z O.O. has the right to equip its classified products with the classification mark and to use this classification mark when marketing these products.

The decision is in line with the requirements laid down in the Classification of Indoor Climate 2018 and the Cleanliness Classification of Air-handling Products: General Rules.

Building Information Ltd



Laura Apilo  
Managing Director



Katri Leino  
Secretary of the  
Classification  
Working Group